

## Cisco RVS4000 4-port Gigabit Security Router: VPN Cisco Small Business Routers

### Highlights

- Secure, high-speed network access for small businesses
- Gigabit Ethernet connections enable rapid transfer of large files
- Advanced security, including intrusion prevention, helps keep assets safe
- Full IPsec VPN capabilities for up to five remote connections

### Product Overview

The Cisco® RVS4000 Gigabit Security Router delivers affordable, highly secure network access and switching capabilities at broadband speed to help enable employees of small businesses like yours safely connect to the resources they need to be productive (Figure 1). Strong security features include a proven firewall with intrusion prevention, virtual private network (VPN) capabilities, and an optional service that helps block malicious websites and control web access to protect your business. An integrated 4-port Gigabit Ethernet switch allows up to four devices to share high-speed connectivity in the office.

**Figure 1.** Cisco RVS4000 Gigabit Security Router



### Features and Benefits

The Cisco RVS4000 Gigabit Security Router offers:

- **High-speed connectivity:** Gigabit Ethernet connections on both WAN and LAN ports help you take full advantage of your broadband connections, enabling your employees to send and receive large files quickly and easily.
- **Proven Stateful Packet Inspection (SPI) firewall with Intrusion Prevention System (IPS):** Unlike standard firewalls, which block incoming streams based only on the source or type of data, the intrusion prevention system scans deep, enabling it to detect and block most worms, Trojan horses, and denial-of-service attacks to help keep your business assets safe.
- **VPN capabilities:** IP Security (IPsec) VPN capabilities built into the RVS4000 enable your remote employees, whether working from home or on the road, to connect to your office network using nearly any VPN client to access files and transfer data as securely as if they were in the office.

- **Optional Cisco ProtectLink Web security service:** This optional hosted service adds another layer of protection to your network by blocking malicious websites and controlling web access, without the drain on your office PCs caused by traditional security solutions.
- **Improved traffic flow and network management:** Flexible, built-in support for up to four 802.1Q virtual LAN (VLAN) connections enable separation of network traffic to help improve traffic flow and overall network management while enabling the RVS4000 to interoperate with other VLAN-capable switches (Figure 2).

**Figure 2.** Cisco RVS4000 Gigabit Security Router Port Connections



**Product Specifications**

Table 1 lists the basic product specifications for the RVS4000 Gigabit Security Router.

**Table 1.** Product Specifications

Feature	Description
<b>Routing</b>	<ul style="list-style-type: none"> <li>• Static routing</li> <li>• Routing Information Protocol (RIPv1 and RIPv2)</li> <li>• Inter-VLAN routing</li> </ul>
<b>Layer 2</b>	<ul style="list-style-type: none"> <li>• Port-based and 802.1Q tag-based VLANs</li> <li>• 4 active VLANs (4094 range)</li> <li>• One of five WAN/LAN ports can be mirrored to a selected LAN port</li> <li>• Supports Rapid Spanning Tree Protocol (RSTP) for loop detection and faster reconfiguration</li> </ul>
<b>Network</b>	<ul style="list-style-type: none"> <li>• Dynamic Host Configuration Protocol (DHCP) Server, DHCP Client, DHCP Relay Agent</li> <li>• DHCP Server supports static IP address based on MAC address</li> <li>• Domain Name System (DNS) Relay, Dynamic DNS (DynDNS, TZO)</li> <li>• Network Address Translation (NAT): Port Address Translation (PAT), Network Address Port Translation (NAPT), Session Initial Protocol (SIP) Application Layer Gateway (ALG) support, NAT traversal</li> <li>• Network edge software configurable on any IP address</li> </ul>
<b>IPv6</b>	<ul style="list-style-type: none"> <li>• Dual-stack IPv4 and IPv6</li> <li>• 6 to 4</li> <li>• Stateless address auto-configuration</li> <li>• DHCP v6</li> <li>• Intra Module Command Protocol ICMP v6</li> </ul>

<b>Security</b>	<p>Access Control</p> <ul style="list-style-type: none"> <li>• MAC-based, IP-based access control list (ACL)</li> </ul> <p>Firewall</p> <ul style="list-style-type: none"> <li>• SPI firewall</li> </ul> <p>Content Filtering</p> <ul style="list-style-type: none"> <li>• Static URL blocking or keyword blocking (included)</li> <li>• Dynamic filtering through Cisco ProtectLink Web security service (optional)</li> </ul> <p>Intrusion Prevention System (IPS)</p> <ul style="list-style-type: none"> <li>• IP sweep detection</li> <li>• Application anomaly detection (HTTP, FTP, Telnet, Remote Copy Protocol [RCP])</li> <li>• Peer-to-peer control</li> <li>• Instant messenger control</li> <li>• Layer 3/Layer 4 protocol (IP, TCP, User Datagram Protocol [UDP], Internet Control Message Protocol [ICMP]) normalization</li> </ul> <p>Secure Management</p> <ul style="list-style-type: none"> <li>• HTTPS</li> <li>• Username/password</li> </ul> <p>802.1X</p> <ul style="list-style-type: none"> <li>• Port-based RADIUS authentication (Extensible Authentication Protocol multicast distributed switching [EAP-MDS], Protected Extensible Authentication Protocol [PEAP])</li> </ul>
<b>VPN</b>	<ul style="list-style-type: none"> <li>• 5 VPN tunnels for remote client access</li> <li>• 5 IPsec gateway-to-gateway tunnels for branch office connectivity</li> <li>• Triple Data Encryption Standard (3DES) encryption</li> <li>• Message Digest Algorithm 5 (MD5)/Secure Hash Algorithm (SHA1) authentication</li> <li>• IPsec NAT=T</li> <li>• VPN pass-through of Point-to-Point Tunneling Protocol (PPTP), Layer 2 Tunneling Protocol (L2TP), IPsec</li> </ul>
<b>Quality of Service</b>	<ul style="list-style-type: none"> <li>• Service-based bandwidth management supports rate control and priority</li> <li>• Port-based prioritization on LAN port; application-based on WAN port</li> <li>• 4 queues</li> </ul>
<b>Management</b>	<ul style="list-style-type: none"> <li>• Simple Network Management Protocol (SNMP) version 1, 2c</li> <li>• Event logging: local, syslog, email alerts</li> <li>• Firmware upgradable through web browser</li> <li>• Flash, RAM diagnostics</li> <li>• Built-in web user interface for browser-based configuration</li> </ul>
<b>Performance</b>	NAT throughput: 800 Mbps when IPS is disabled
<b>Warranty Information</b>	
<p>This Cisco Small Business product comes with 3-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to <a href="http://www.cisco.com/go/smallbiz">http://www.cisco.com/go/smallbiz</a>.</p>	

## System Specifications

Table 2 lists the system specifications of the RVS4000 Gigabit Security Router.

**Table 2.** System Specifications

Feature	Description
<b>WAN</b>	Gigabit Ethernet (10/100/1000) WAN port
<b>LAN</b>	4-port, full-duplex 10/100/1000 Ethernet switch
<b>Physical dimensions and weight</b>	<ul style="list-style-type: none"> <li>• W x D x H = 6.69 in. x 1.61 in. x 6.69 in. (170 mm x 41 mm x 170 mm)</li> <li>• Weight: 0.84 lb (0.38 kg)</li> </ul>
<b>Power</b>	12V 1A
<b>Approvals and compliance</b>	<ul style="list-style-type: none"> <li>• IEEE 802.3/802.3u</li> <li>• IEEE 802.1X (security authorization)</li> <li>• RFC 791 (IPv4)</li> <li>• RFC 2460 (IPv6)</li> <li>• RFC 1058 (RIPv1)</li> <li>• RFC 1723 (RIPv2)</li> </ul>

<b>Certification</b>	<ul style="list-style-type: none"> <li>• FCC Class B</li> <li>• CE</li> <li>• ICES-003</li> </ul>
<b>Environmental operating range</b>	<ul style="list-style-type: none"> <li>• Operating temperature: 0° to 40°C (32° to 104° F)</li> <li>• Storage temperature: -20° to 70°C (-4° to 158°F)</li> <li>• Operating humidity: 10 to 85% relative humidity (noncondensing)</li> <li>• Storage humidity: 5 to 90% relative humidity (noncondensing)</li> </ul>

## Configuration Requirements

Table 3 lists the minimum requirements that must be in place in order to install or use the product.

**Table 3.** System Requirements

Feature	Description
<b>Network adapter</b>	Network adapter with Ethernet network cable installed per PC
<b>Web-based configuration</b>	Java/cookies/SSL-enabled web browser

## Ordering Information

Table 4 lists ordering information for the Cisco RVS4000 Gigabit Security Router and optional Trend Micro ProtectLink Gateway Security Service.

**Table 4.** Ordering Information

Part Number	Product Name
<b>RVS4000</b>	Cisco RVS4000 Gigabit Security Router (USA)
<b>RVS4000-AU</b>	Cisco RVS4000 Gigabit Security Router (Australia/New Zealand)
<b>RVS4000-EU</b>	Cisco RVS4000 Gigabit Security Router (Europe)
<b>RVS4000-UK</b>	Cisco RVS4000 Gigabit Security Router (United Kingdom)
<b>RVS4000-AS</b>	Cisco RVS4000 Gigabit Security Router (Asia Pacific)
<b>RVS4000-SG</b>	Cisco RVS4000 Gigabit Security Router (Singapore)
<b>RVS4000-LA</b>	Cisco RVS4000 Gigabit Security Router (Latin America)
<b>Security Service</b>	
<b>L-PL-WEB-1=</b>	1-year subscription to Cisco ProtectLink Web security service
<b>L-PL-WEB-3=</b>	3-year subscription to Cisco ProtectLink Web security service



Americas Headquarters  
Cisco Systems, Inc.  
San Jose, CA

Asia Pacific Headquarters  
Cisco Systems (USA) Pte. Ltd.  
Singapore

Europe Headquarters  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)